Technical Data





BR3DGN01-CONCEPT Daylight **Precision Concept** 3D polymers

SPECS

FEATURES

Precision Concept has been designed for creating high definition jewellery parts especially for the Precision Printer. The printed parts will display a high tensile strength and durability, as well as a high accuracy and detail for the use in the modern jewellery market. This resin will allow designers to display highly accurate and detailed jewellery models. In addition, the high print speed of this resin, will allow jewellers to try their designs directly on the customer's hands. The printed parts will display a smooth surface and a good surface finish. Moreover, patterns can be easily painted with an aerobrush.

Key benefits include high tensile strength, high print speed, high accuracy, smooth surface, easy to use and finish.

PROCESSING INSTRUCTIONS

Follow procedure laid out in your 3D Liquid Crystal's user manual. Polymer should be poured into the tray away from direct sunlight. Polymer can be reused but should be poured through a filter to remove solid lumps. Keep hood on at all times. Liquid polymer is soluble in water and soap. In order to clean the printed objects, we recommend Photocentric's Resin Cleaner, or IPA, followed by water. The cleaned objects should be post exposed at 80°C under UV for a minimum of 1 hour to obtain the maximum tensile properties. Alternatively, the parts can be post exposed on water under UV for 30 minutes.

IDEAL APPLICATIONS

Jewellery



DATA

Viscosity
(At 25°C Brookfield spindle 3)690cPsHardness92 Shore DASTM D2240 (After post exposure)

Tensile strength45 MPaASTM D638 (After post exposure, 1h UV)

Elongation at break 2% ASTM D638 (After post exposure, 1h UV)

Storage Density 10<t>50°C 1.1 g/cm³

AVAILABLE COLOURS

Green

Available in 1kg bottles.

Photocentric Ltd. Cambridge House, Oxney House Peterborough PE1 5YW **UK** email: *info@photocentric.co.uk* Photocentric Inc. 2205 West Parkside Lane, Phoenix, 85027, AZ **USA** email *info@photocentricusa.com*